

Product Information	
Date:	26-01-2015
Code:	6140122
Name:	Procar Underbody coating
Version TDS:	001
Product group:	Painting
Application:	High quality preservative to treat the underside of vehicles.
Properties:	Remains flexible Excellent adhesion Resistant to weather influences Resistant to weak acids and bases Excellent corrosion prevention Sound-absorbing
VOC-content:	Approximately 70% w/w
Color:	Black
Dust dry:	After 60 minutes
Directions for use:	<p>Before use, carefully read the directions on the packaging and act accordingly.</p> <p><b>Pre Treatment</b> The surface should be clean, dry and free of grease. Remove loose old lacquer and rust.</p> <p><b>Treatment</b> The surface should be clean, dry and free of grease. The aerosol should have room temperature. Best processing temperature 15 to 25°C. Before use, shake the aerosol for 2 minutes and spray a sample. Distance to the surface to be treated approximately 25 to 30 centimetre. Apply the UNDERCOATING in several thin layers. After use, clean the valve (turn aerosol upside down and press the nozzle for approximately 5 seconds). The drying time depends on the ambient temperature, the humidity of the air and the thickness of the lacquer applied.</p>
Safety:	See MSDS
	Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Pressurized container: Do not pierce or burn, even after use. Do not spray on an open flame or other ignition source. Avoid breathing spray. Wear protective gloves / eye protection. Use only outdoors or in a well ventilated area.
Application temperature:	10°C – 35°C
Storage conditions:	Cool (10°C – 20°C) and dry
<p>This information was composed to the best of our current knowledge. It provides no guarantees. The data in this sheet is a result of extensive testing either by Mobacc or its suppliers. However always thoroughly check whether the product is fit to serve the purpose you mean it to work for.</p>	